

CouponXpress™

desktop TITO/coupon printer



RELIABLE PERFORMANCE

- ITH® (Intelligent Ticket Handling) technology virtually eliminates ticket jams by making ticket available only after it's been fully printed and burst

FAST PRINTING SPEED

- Prints and presents in 3.8 seconds

LARGE FILL CAPACITY

- Stores up to 300 tickets

EXPANDED GRAPHICS MEMORY

- Stores a wide range of clip art objects and thousands of templates

The CouponXpress™ desktop TITO/coupon printer builds on the technology that has made JCM the leading manufacturer of TITO printers – bringing all of the popular GEN2U™ and GEN5™ printer features, functions and flexibility from the game to the cashier's cage, hotel front desk, unattended kiosks and other transaction points.

Compatible with traditional gaming protocols as well as new USB communications, the CouponXpress printer enables fast, convenient TITO transactions, such as ticket purchases, consolidation, or replacement of torn or crumpled tickets. It can also be used to distribute targeted promotional coupons at different venues – such as at the concierge desk, gas station, gift shop, or hotel rooms – to reward, retain or recruit casino patrons.

Housed in an attractive and rugged cabinet, the CouponXpress printer provides the convenience, flexibility and reliable performance needed for effective coupon campaigns.

Fast 3.5 inch per second printing, large ticket storage capacity, and ITH® (Intelligent Ticket Handling) technology combine to maximize the CouponXpress printer's uptime and reliability. Additionally, high-resolution printing and storage for a wide range of clip art objects and thousands of templates facilitates ticket customization and branding.

GENERAL SPECIFICATIONS

Dimensions (WxDxH)
147.3mm x 372.1mm x 111.2mm

Weight
1.23kg (2.7lbs.)

Power requirements
110Vac via 24Vdc @ 2.7A external power supply (power supply sold separately)

Sensors
Paper low, paper out, printer drawer open, ticket taken, ticket jam, ticket in chute, black mark

Printing speed
90mm/second (3.5"/second)

Print and present
3.8 seconds standard
3.0 seconds with ICB

Printing width
62mm (true near-edge printing)

Storage
300 tickets

Resolution
8 dots/mm (203 dpi)

Firmware
Application in memory is reprogrammable (via Flash BIOS)

Self test
Yes

Page mode
Full page mode printing (simultaneous 4 orientation printing: 0°, 90°, 180°, 270°), line and box draw printer resident, bitmap graphics, printer resident (stored in Flash) graphics

Paper loading
Manual

Paper feed
Auto load

Media
Direct thermal, top coated, fanfolded and perforated

Paper specification
66mm W x 156mm L
4.5mil, 1 color

Bezel control
Lighted, two high current ticket printing bezel control ports

User Interface
4 LED indicators, paper advance button (located on the printer)

Upgrade port
Allows for printer upgrades via rear or internal USB upgrade port

Cabinet
Lockable; comes standard in glossy black finish, other finishes available at additional cost

Hot swappable
100%

PRINTING RESOURCES

Template capacity
4Mb; stores a wide range of clip art objects and thousands of templates

Graphic storage
4Mb

CHARACTERISTICS

Printer languages
TCL printer language (page description language) Subset of ESCP2

Fonts
8 (2.5 cpi, 3.3 cpi, 4.0 cpi, 5.5 cpi, 5.6 cpi, 7.3 cpi, 10.1 cpi, 20.5 cpi)

Font scalability
May be independently scaled from 1x – 7x in both height and width

Barcodes
PDF-417, Interleaved 2 of 5, Code 39, UPC-A, UPC-E, UPC-E+2, UPC-E+5, Codabar, EAN-13, EAN-8, Code 128, MSI, Data Matrix

Memory
8MB with 512K RAM

INTERFACE

Communications
Bi-directional RS232C USB 2.0 game interface (full speed of 12Mbps) with separate USB download port, GSA compliant

ENVIRONMENTAL

Operating temperature
0°C to 65°C

Storage temperature
-20°C to 75°C

Operating humidity
5 to 85% RH non-condensing

RELIABILITY

Maintenance
Annual print head cleaning required

Print head life
100km min. (656,000 tickets based on standard size TITO tickets)

Certifications
ISO 9001, CE certified, RoHS

COVER OPTIONS

